


80mm Classic Thermal Receipt Printer 80250IVN



- 1) 250mm/s high print speed
- 2) Multiple language fonts selectable
- 3) Multiple interfaces
- 4) Low power consumption and low operation cost



Key Features

- Compatible with EPSON ESC/POS and STAR command sets
- Support paper near end and black mark detection
- Connect and print faster, stop receipt misprinting
- Support connecting to WLAN printing
- Virtual serial port mode, USB port support OPOS application
- 250mm/sec ultra high print speed
- Built in Web page to set up printer directly
- Printer status monitoring
- High speed driver printing mode,66% improvement in print
- Windows X86 / X64 / Linux / OPOS driver
- Support up 68 international languages and GB18030
- Serial+USB+Ethernet, Parallel+USB interfaces
- Support IP change via Serial or USB port



Specification

| | |
|---------------------|--|
| Print method | Direct thermal line |
| Print width | 64/76mm |
| Dot density | 512/576dot/line |
| Print speed | 250mm/s |
| Interface | Serial+USB+Ethernet, USB+Parallel |
| Paper diameter | 80mm |
| Line space | 3.75mm(can be adjustive) |
| Character Size | ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/Traditional Chinese Character: 24×24dots |
| Code page | PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/ WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| Barcode type | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128/ QRCODE |
| Fonts | GB18030 |
| Data | 128K bytes |
| NV Flash | 256K bytes |
| Cashdrawer out | DC 24V/1A |
| Power supply | AC 110V/220V 50 ~ 60Hz DC 24V/2.5A |
| Weight | 1.65kg |
| Dimension | 195×160×145mm |
| Work environment | Temperature:0 ~ 45°C, Humidity:10 ~ 80% |
| Storage environment | Temperature:-10 ~ 60°C, Humidity:10 ~ 90% |
| Auto Cutter | 1.5 million |