

RhinoMobility RM-iF4200 /iF4300



4inch Direct Thermal & Thermal Transfer Barcode Printer

KEY FEATURES


- High-performance barcode printer with rich expansion capabilities
- Thermal transfer and thermal dual-mode automatic switching
- Fast 8IPS print speed at 203dpi print resolution, 6IPS at 300dpi version (**RM-iF4300**)
- Pre-installed multiple emulation for easy system integration (EPL, EPL 2, ZPL, ZPL II, DPL, TSPL)
- Flexible connectivity: USB+Ethernet
- RFID version works with jewelry label, flexible anti-metal RFID assets label, as factory option
- Bartender Ultralite available to edit and print your labels
- Driver, SDK, user guide, video, FAE support available



Peeler




Regular Cutter



Textile-care Cutter

4inch Direct Thermal & Thermal Transfer Barcode Printer

MODEL	RM-IF4200	RM-IF4300
Level	Standard	Standard
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal	
Max. print speed	203mm(8")/second	152mm(6")/second
Max. print width	108 mm (4.25")	106 mm (4.17 ")
Memory	128 MB	
Interface	• USB 2.0 High Speed 480Mbps • Internal Ethernet 10/ 100Mbps • Internal Bluetooth 5.2 (distributor option) • Internal WiFi (distributor option)	
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz. Output: DC 24V, 2.5A, 60W	
Internal fonts	•8 alpha-numeric bitmap fonts •True type font engine (need to download scalable font file)	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Plessy, PostCode, Telepen	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
Printer language	Compatible to TSPL, EPL, EPL 2, ZPL, ZPL II, DPL	
Physical dimension	282mm(W) * 168 mm(H) * 175 mm(D)	
Net Weight	2.3kg	



Accessories

- Windows labeling software CD disk
- Quick start guide
- USB cable
- Power cord
- 1" ribbon spindle x 2 for 300M ribbon
- External universal switching power supply

Enclosure

Clamshell with double-walled plastic

Applications:

- Shipping
- Warehousing
- Retail
- Library
- Logistics
- Transportation
- Restaurant fast food service
- Ticketing
- Manufacturing
- High-value assets tracking

Safety regulation

Comply with RoHS, REACH, WEEE

Safety regulation

FCC Class A, CE Class A, CCC, BIS, CB

